

P65-17-XDHH-R**iRET Tri Broadband Cross Polarized
790-960/2x1710-2170MHz, 2.0m**


POLARIZATION: XXX-Pol
 FREQUENCY (MHz): 790-960, 2x1710-2170
 HORIZONTAL BEAM WIDTH (°): 65
 GAIN (dBi dBd): 16.2/14.1, 16.5/14.4, 16.5/14.4
 TILT: 0-16°/0-12°/0-12°
 LENGTH: 2.0m(6'6")

ELECTRICAL SPECIFICATIONS*

	790-960		2x1710-2170		
	790-894	880-960	1710-1880	1850-1990	1920-2170
Frequency range (MHz)					
Frequency band (MHz)	790-894	880-960	1710-1880	1850-1990	1920-2170
Gain (dBi/dBd)	15.6/13.5	16.2/14.1	16.0/13.9	16.1/14	16.5/14.4
Polarization	Dual linear ±45°		Dual linear ±45°		
Nominal Impedance (Ω)	50		50		
VSWR	<1.5:1		<1.5:1		
Horizontal beam width, -3 dB (°)	73	67	65	63	60
Vertical beam width, -3 dB (°)	9.6	8.6	10	9.4	8.7
Electrical down tilt (°)	0-16		0-12		
Side lobe suppression, vertical 1st upper (dB)	>18,17,16,16@ 2,5,7,8	>18,17,16,16@ 2,5,7,8	>17,15,13@ 0,6,10	>17,15,14@ 0,6,10	>17,16,15@ 0,6,10
Isolation between inputs (dB)	>30	>30	>30	>30	>30
Inter band Isolation (dB)	>34		>34		
Tracking, horizontal plane ±60° (dB)	<1.5	<2	<2	<2	<2
First null fill (dB)	25	25	25	25	25
Vertical beam squint (°)	0.5	0.5	0.5	0.5	0.5
Front to back ratio (dB) 180° ±30° copolar	>28	>30	>27	>28	>30
Front to back ratio (dB) 180° ±30° total power	>25	>25	>25	>25	>25
Cross polar discrimination (XPD) 0° (dB)	16	15	16	16	15
Cross polar discrimination (XPD) ±60° (dB)	>11	>9	>7	>6	>6
Far field coupling	<0.27	<0.47	<0.52	<0.66	<0.66
IM3, 2xTx&43dBm (dBc)	<-153		<-153		
IM7, 2xTx&43dBm (dBc)			<-160		
Power handling, average per input (W)	300		250		
Power handling, average total (W)	600		1000		

MECHANICAL SPECIFICATIONS*

Connector	6x 7/16 DIN Female
Connector position	Bottom
Dimensions, HxWxD, mm(ft)	2033x280x155mm (6'8"x11"x6")hk
Mounting	Pre-mounted standard brackets
Weight, with brackets, kg (lbs)	21.9 (48.2)
Weight, without brackets, kg (lbs)	16.4 (36.1)
Wind load, frontal/lateral/rear side 42 m/s Cd=1.6 (N)	653 / 128 / 785
Maximum operational wind speed, m/s (mph)	42 (93)
Survival wind speed, m/s (mph)	55 (123)
Lightning protection	DC grounded
Operating Temperature	-40°C to +60°C
Radome Material	ASA
Radome colour	Light Grey
Packing size, HxWxD, mm (ft)	2175x355x255 (7'2"x14"x10")
Shipping weight, kg (lbs)	26.5 (58.4)
RET	3x8510.40 factory attached (AISGv2.0)
Brackets	7256.00,7454.00A



*All specifications subject to change without notice. Please contact your Powerwave representative for complete performance data.

ANTENNA PATTERNS*

For detailed patterns visit <http://www.powerwave.com/rpa/>.